

# COLUMN & BOOM MANIPULATORS



Model	Clear Strokes in meters		Up-Down Speed mm/min	Fw.-Rev. Speed mm/min	Base	Rail Gauge mm	Trolley Speed mm/min	Max. load at boom end Kg	Overall Height mm	Column Swivel
	Ver.	Hor.								
SRT-CB1010	1	1	1000	125-1250	Pedestal/ Fixed, manual trolley or motorized trolley	1200	1500	150	3000	360 Degrees manual or motorized swivel
SRT-CB1515	1.5	1.5						150	3500	
SRT-CB2020	2	2						150	4000	
SRT-CB3030	3	3						150	5000	
SRT-CB4040	4	4				200		6250		
SRT-CB5050	5	5				200		7300		
SRT-CB6060	6	6				200		8500		
SRT-CB7070	7	7				250		9750		
SRT-CB8080	8	8	250	11000						

## NOTES :

- a) Custom Built Column & boom manipulators as per stroke requirements can also be provided apart from the standards.
- b) Ladder included.
- c) Manual Column Swivel 360 degree.
- d) Anti fall arrangement adopted for all models.
- e) We reserve the right to modify the dimensions & others as per new design developments.

## OPTIONAL ACCESSORIES :

- a) X-Y Cross Slides
- b) Welding Head & Power Source.
- c) Without trolley base.
- d) Flux recovery unit.
- e) Trolley cable trailing arrangement.
- f) Operator platform.