

SELF CENTERING ROTATORS



Model	Turning Capacity Metric Tonnes	Load Capacity Metric Tonnes		Roller Surface Speed mm/min	Job Diameter Range	Roller Size mm		Roller Type
		Drive unit	Idler unit			Diameter	Width	
SRT-SCR02	2	1	1	125 - 1250	300 - 1500	200	50	PU COATED
SRT-SCR05	5	2.5	2.5		400 - 4000	300	100	
SRT-SCR10	10	5	5		500 - 5000	400	100	
SRT-SCR15	15	7.5	7.5		500 - 5000	400	120	
SRT-SCR20	20	10	10		500 - 5000	400	150	
SRT-SCR30	30	15	15		500 - 5000	400	200	
SRT-SCR40	40	20	20		500 - 5000	500	175	
SRT-SCR50	50	25	25		500 - 5000	500	200	
SRT-SCR60	60	30	30		500 - 5000	500	250	
SRT-SCR80	80	40	40		500 - 5000	500	275	
SRT-SCR100	100	50	50		500 - 5000	500	300	
SRT-SCR120	120	60	60		500 - 5000	500	300	STEEL
SRT-SCR150	150	75	75		500 - 5000	550	250	
SRT-SCR200	200	100	100		1000 - 6000	550	250	
SRT-SCR250	250	125	125		1000 - 6000	550	300	
SRT-SCR300	300	150	150		1000 - 8000	650	200	
SRT-SCR500	500	250	250	1000 - 8000	650	250		

NOTES :

- Custom Built self centering rotators can also be provided apart from the standards.
- We reserve the right to modify the dimensions & others as per new design developments.

OPTIONAL ACCESSORIES :

- Ratchet spanner for Screw.
- Without lead screw i.e. Conventional Type Rotator.
- Manual or Motorized Trolley/Bogie mounted.
- Skew arrester to avoid longitudinal displacements.
- Roller material as per requirement.
- Synchronization of two or more drive unit rotators.
- Totally covered system for Blasting or Painting application.